



TECHNICAL PAINT SERVICES

A30 FLOOR FINISH ALKYD

Features:

A high quality, moderately priced lead free synthetic floor finish suitable for interior or exterior use. Resistant to water, common engineering oil, petrol and light chemicals. Ideal for use on weathered concrete, wood, metal and timber floors, and can be applied over most existing paints without lifting. This paint should not be applied over PVA sealer, latex self leveling compound or power floated concrete. Please contact our Technical Department. AG30 Contract Grade available, minimum 25 Litres.

Availability:

All BS4800 colours plus Clear in 5 Litre containers. A31 Floor Finish Alkyd Non-Slip is also available. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

55% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. Concrete floors must be at least 6 months old before application of A30. For newer concrete, please contact our Technical Department.

Application:

By brush, roller or spray. Supplied ready for use for brushing. Thin up to 25% by volume, with UTR112 Universal Synthetic Thinners, for roller or spray application. Do not use when air temperature is below 5°C, or during high humidity.

Coverage:

40 sq metres per 5 Litres per coat @ 25 microns dry film thickness.

Drying:

Touch dry: 6 - 8 hours @ 20°C.

Recoat after overnight drying.

Light foot traffic after 24 hours.

Full use: 2 - 3 days.

Health & Safety: Please see MSDS sheet **100D4**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

A30 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.