

## AS56/5 ALKALI RESISTING PRIMER, OFF-WHITE

### Features:

A specially formulated primer, based on alkyd resin, which resists the alkali present in new concrete and plaster. It is also suitable as a sealer for asbestos and cement sheeting.

## Availability:

In 5.0 and 2.5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

#### Volume Solids:

 $51\% \pm 3\%$  (BS 3900 Part A10).

#### Preparation:

The substrate should be thoroughly clean, dry and free from dust and grease. Concrete and plaster must be at least 7 days old. Lime wash, distemper or cementatious paints must be removed before application of the primer.

### Application:

Brush or conventional spray. Supplied ready for use for brushing. For spraying, thin up to 5% by volume with White Spirit.

#### Coverage:

Approximately 40 - 60 sq metres per 5.0 Litres depending on porosity of substrate.

# Drying:

Touch dry: 4 hours @ 20°C.

Recoatable with oil based or emulsion paints after overnight drying.

Health & Safety: Please see MSDS sheet 100D4.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

AS565 04 14

## FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.