



TECHNICAL PAINT SERVICES

H45/60 HEAT RESISTING QUICK DRYING BRIGHT ALUMINIUM

Features:

A general purpose, quick drying, bright aluminium paint with excellent heat resistance up to 250°C. Suitable for application to ferrous metals and timber.

Availability:

5 and 2.5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

55% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. For optimum durability it is recommended that ferrous substrates are treated with UP89 Two Pack Etching Primer prior to application of H45/61.

Application:

Do not apply to heated surfaces, cool before applying by conventional or airless spray. Small areas may be brushed. Thin up to 20% by volume, using UTR112 Universal Synthetic Thinners to achieve a spraying viscosity of 25 - 30 seconds BSB4 cup @ 20°C.

Note:

Some difference in brightness and general appearance can be anticipated between brush and spray application and therefore mixed methods of application are not recommended.

Coverage:

Approximately 60 sq metres per 5 Litres depending on surface.

Drying:

Touch dry:	5 - 8 minutes @ 20°C.
Hard dry:	40 - 45 minutes @ 20°C.
Full properties:	7 days.

Health & Safety: Please see MSDS sheet **10019**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

H4560 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 01202 295 552
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.