

# X85 MORDANT SOLUTION

#### Features:

A pre-treatment for new, galvanised surfaces. The treatment etches the surface of the metal to provide a key for subsequent coats of paint and varnish.

## Availability:

5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

#### **Volume Solids:**

N/A.

#### Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

## Application:

Brush liberally onto galvanised surfaces and leave for 1 hour for the solution to react. A black deposit will be formed when the reaction is complete. The surface should then be washed off with clean tap water to remove any zinc salts and dried thoroughly before the application of a primer, which should be applied within 2 hours.

# Coverage:

Approximately 100 sq metres per 5 Litres.

Health & Safety: Please see MSDS sheet 100N14.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

X85 04 14