



TECHNICAL PAINT SERVICES

CONTRACT GRADE CHLORINATED RUBBER PAINT, RG10

Features:

An air drying, contract grade single pack system resistant to a wide range of chemicals, including acids, alkalis, oxidising agents, inorganic salts, moist gases and mineral oil. Having excellent exterior durability and heat resistance up to 75°C, RG10 is ideally suited for application to chemical storage tanks, bridges, marine equipment, swimming pool surrounding walls and ceilings, sewage tanks, skips and ships containers etc. RG10 is also suitable for application to newly laid concrete which has been allowed to weather for 3 - 4 weeks. Made to a budget price for larger, price sensitive applications.

Availability:

Limited BS4800 colours, made to order in a minimum of 25.0 Litre quantities. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

51% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be clean, dry and free from corrosion, dust and grease. RG10 may be applied over RPG10 Contract Chlorinated Rubber Primer, APG79 Universal Primer, AP83/65 Zinc Rich Galvanic Primer, UP89 Two Pack Etching Primer, WBP1010 Universal Adhesion Surface Primer, WBP1020 Two Pack Epoxy Primer or PP129 Adhesion Promoter.

Application:

Brush, roller, or airless spray. Supplied ready for use for brushing. Thin up to 20% by volume with XTR112 Contract Universal Synthetic Thinners to achieve a spraying viscosity of 30 seconds BSB4 cup @ 20°C. We recommend a 1.9 Thou' airless tip size at 2000psi.

Coverage:

40 sq metres per 5 Litres depending on surface profile.

Drying:

Touch dry:	30 - 40 minutes @ 20°C. 3 hours @ 10°C.
Recoatable:	8 hours @ 20°C. 12 hours @ 10°C.

Health & Safety: Please see MSDS sheet **10019**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

RG10 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.